






1. 额定电压: 250V, 额定电流: 15A
2. 间距: 5.0mm
3. 耐电压值: AC 2500V/min
4. 使用条件: $-40^{\circ} - +105^{\circ}$
5. 适用线规: 26-12AWG
6. 螺丝扭力: 0.5Nm

5	LC1-5.08螺丝 (一字平头)		SPOYA255301V		2	碳钢	三价铬钝化彩锌	
4	LC1-5.08铜方块		F1A0BLG1283V		2	黄铜	镀镍	
3	LGV3A-5.0-中焊脚		LGV3A-5.0-中焊脚		1	黄铜	镀雾锡	
2	LGV3A-5.0-小焊脚		LGV3A-5.0-小焊脚		1	黄铜	镀雾锡	
1	LGAKD-5.0-主体 (M3孔)		LGAKD-5.0-主体 (M3孔)		1	PA66		
NO.	NAME OF PART		NO. OF PART		Q'TY	MATERIAL	NOTES	
DES.	CMZ	DATE	2026/09/01	UNITS	MM			SHEET
CHK.		DATE		SIZE	A4			1 of 1
APP.		DATE		SCALE	1:1	DWG NO.	SP-2-2030001	REV:VC
 上海联捷电气有限公司 Shanghai Elinker Electric CO.,LTD						TITLE	LGAKD-5.0-2P-1Y-00A-左脚 (M	
							LGAKD-5.0-成品	