

XCFR8.E340097 - Terminal Blocks Certified for Canada - Component

Terminal Blocks Certified for Canada - Component

SHANGHAI ELINKER ELECTRIC CO LTD


87 Zhuxi
Zhuao Town
Sanmen
Taizhou, Zhejiang 317101 China

E340097

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
LW1-7.62	14-22 SOL/STR	Cu	.508	300	15	B,D	2(115)
LW1-8.25	12-22 SOL/STR	Cu	.508	300	20	B	2(115)
LW3-9.52	12-22 SOL/STR	Cu	1.19	300	20	B	2(115)
LW2-9.5	12-22 SOL/STR	Cu	1.47	300	20	B,C	2(115)
LW3-8.25B	12-22 SOL/STR	Cu	.486	300	20	B	2(115)
LG135-10.16	20-6 SOL/STR	Cu	1.41	300	52	B,C,D	2(115)
LG127-5.0	26-16 SOL/STR	Cu	.396	300	8	B	2(115)
LG129	26-12 SOL/STR	Cu	.407	300	18	B	2(115)
LG128	26-12 SOL/STR	Cu	.407	300	15	B	2(115)
LG103-5.0	28-12 SOL/STR	Cu	.407	300	15	B	2(115)
LS250-3.5	22-18 SOL/STR	Cu	—	300	5	B,D	2(115)
LC1-5.08	28-12 SOL/STR	Cu	.497	300	15	B	2(115)
LC1-3.81	28-16 SOL/STR	Cu	.192	300	8	B	2(115)
LZ1V-5.08	N/A	N/A	N/A	300	15	B	2(115)
LZ1R-5.08	N/A	N/A	N/A	300	15	B	2(115)
LC12-3.81	N/A	N/A	N/A	300	8	B	2(115)
LZ3H-3.81	N/A	N/A	N/A	300	8	B	2(115)
LZ1-3.81	N/A	N/A	N/A	300	8	B	2(115)
LC1-3.5, LC1M-3.5	16-28 AWG, Str/Sol	Cu	0.2	300	8	B, D	2(105)
LC2-3.81, LC2M-3.81	14-30 AWG, Str/Sol	Cu	0.2	300	8	B, D	2(105)

LC1-5.0, LC1M-5.0	12-24 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(105)
LC2-5.08, LC2M-5.08	12-30 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(105)
LC6-2.5	20-24 AWG, Sol	Cu	-	150	4	B	2(105)
LC6-3.5, LC6M-3.5	16-28 AWG, Sol	Cu	-	300	8	B, D	2(105)
LC6-5.08, LC6M-5.08	12-26 AWG, Sol	Cu	-	300	10	B, D	2(105)
LC10, LC10M, LC10MG	12-24 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(105)
LW1B, LW1C, LW1MB, LW1MC, LW1Q, LW1R, LW1MQ, LW1MR	12-22 AWG, Str/Sol	Cu	1.2	300	20	B, D	2(120)
LW3, LW3M	14-22 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(120)
LW6C, LW6MC, LW6Q, LW6MQ	14-22 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(120)
TB1-15	14-22 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(115)
TB1-25	10-22 AWG, Str/Sol	Cu	1.2	300	25	B, D	2(115)
JHY1-16A	16-22 AWG, Str/Sol	Cu	0.5	600	10	B, C, D	2(105)
JHY1-25A	12-24 AWG, Str/Sol	Cu	1.2	600	20	B, C, D	2(105)
LG300	14-22 AWG, Str/Sol	Cu	0.5	300	10	B, D	2(105)
LG381	16-26 AWG, Str/Sol	Cu	0.2	300	8	B, D	2(105)
LG635	10-24 AWG, Str/Sol	Cu	0.5	300	30	B, D	2(105)
ULUK2.5B	12-24 AWG, Str/Sol	Cu	0.5	600	20	B, C, D	2(105)
ULUK5N	10-24 AWG, Str/Sol	Cu	0.5	600	30	B, C, D	2(105)
YL1, YL1M	12-28 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(105)
PT1, PT1M	12-28 AWG, Str/Sol	Cu	0.5	300	15	B, D	2(105)
LZ1V-2.5, LZ1R-2.5	-	-	-	150	4	B	2(105)
LZ1V-3.5, LZ1R-3.5, LZ1VM-3.5, LZ1RM-3.5, LZ3HM-3.81	-	-	-	300	8	B, D	2(105)
LZ1V-5.0, LZ1R-5.0, LZ1VK-5.0, LZ1RK-5.0, LZ1VM-5.0, LZ1RM-5.0, LZ3HM1-5.08,	-	-	-	300	15	B, D	2(105)

LZ3HM2-5.08							
LW2-7.9-5+11.0-2-1Y-00A, LW2L-7.9-5+11.0-2-1Y-00A	24-8 AWG, Str/Sol for M4	Cu	1.8	300	38	B,C	2(125)
					30	B,C	
					Note A	D	
	26-14 AWG, Str/Sol for M3	Cu	0.8	300	15	B,C	
					Note A	D	
LW2-7.9-5-1Y-00A	26-12AWG Str/Sol	Cu	0.8	300	20	B,C	2(125)
					Note A	D	
<p>Note A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.</p>							

Marking: Company name and the Recognized Component Mark for Canada  on the product. Catalog designation, maximum voltage, wire range and ampere rating appear on the device or in or on the carton.

Last Updated on 2022-09-15

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."